

Package: qrfactor (via r-universe)

September 16, 2026

Type Package

Title Simultaneous Q-Mode and R-Mode Factor Analysis for Spatial Data

Version 1.6

Date 2026-08-10

Description Performs Q-mode and R-mode factor analysis simultaneously on spatial and non-spatial data. A single function, `qrfactor()`, carries out principal component analysis, R-mode factor analysis, Q-mode factor analysis, simultaneous R- and Q-mode factor analysis, principal coordinate analysis and multidimensional scaling. Loadings and scores are returned from the fitted object, and the `plot()` method provides annotated biplots for combinations of eigenvectors, loadings and scores. Input may be supplied as an 'ESRI' shapefile, a delimited text file or a data frame.

License GPL-2

URL <https://gowusu.github.io/qrfactor/>,
<https://github.com/gowusu/qrfactor>

BugReports <https://github.com/gowusu/qrfactor/issues>

Depends R (>= 3.5.0)

Imports methods, sp, cluster, mvoutlier, pvclust

Suggests MASS, sf

Encoding UTF-8

NeedsCompilation no

Author George Owusu [aut, cre]

Maintainer George Owusu <owusugeorge@ug.edu.gh>

Repository <https://gowusu.r-universe.dev>

Date/Publication 2026-09-06 20:07:11 UTC

RemoteUrl <https://github.com/gowusu/qrfactor>

RemoteRef HEAD

RemoteSha 48e5d4e07de501b26955d828a38aa83fb73ea93a

Contents

qrfactor	2
rq	5
Index	7

qrfactor	<i>Simultaneous Q-Mode and R-Mode Factor Analysis</i>
----------	---

Description

The qrfactor function performs simultaneous Q-mode and R-mode factor analysis on spatial and non-spatial data.

Usage

```
qrfactor(source, layer='', var=NULL, type='', p="Yes", scale="sd", t='',
         nf=2, m=NULL, f=NULL, rotation=FALSE, ...)
## Default S3 method:
qrfactor(source, layer='', var=NULL, type='', p="Yes",
         scale="sd", t='', nf=2, m=NULL, f=NULL, rotation=FALSE, ...)
## S3 method for class 'qrfactor'
print(x,...)
## S3 method for class 'qrfactor'
summary(object,...)
## S3 method for class 'qrfactor'
plot(x,factors=c(1,2),type="loading",plot="",
     cex="",pch=15,pos=3,main="",xlim="optimise",
     ylim="optimise",abline=TRUE,legend="topright",legendvalues=c(100),
     values=FALSE,nfactors=3,rowname=TRUE,par=c(1,2),verbose=FALSE,...)
```

Arguments

source	Folder path of the layer. Please quote the full folder path with forward slash "/". You can use R object as a source but you must set the layer parameter to "nofile"; see below
layer	The layer qrfactor in the folder that you want to work with. It is the file name of qrfactor. This is case sensitive, please. In case you want to use non spatial data such as ".csv", ".txt", "dat" or ".tab" insert the full file name as layer. In case of using R object as a source set "layer" parameter to "nofile"
var	The attributes or variables of the layer. In case of using non spatial data such as ".csv", ".txt", "dat" or ".tab" var are variables or column names
type	Types of plots 'mds' for multidimensional scale, 'coordinate' for principal co-ordinate analyse. Or The type of results one wants to plot. It takes "scores", "loadings", pca or eigenvectors. The default is loadings.

p	Determine whether prediction must be done: "Yes". The scores are appended to the GIS data
t	The list of variables that one wants to transform eg. transform=c("gold", "diamond")
scale	scale the data: "sd", "pca", "data". The default is "sd" that is the scaled data divided by the standard deviation. It can also take "log" or "sqrt" and use the default "sd" for normal distribution transformation
rotation	Should the retained factors be rotated to simple structure? The default FALSE (equivalently "none") returns the classical unrotated solution; TRUE (equivalently "varimax") applies an orthogonal varimax rotation to the first nf factors. When rotation is requested the same orthogonal rotation is applied to the R-mode and Q-mode loadings, so both modes stay on one common set of axes and the scores, the combined loadings, the appended index columns and every biplot and map are rotated consistently. The raw eigenvectors, eigenvalues and PCA loadings (eigen.vector, eigen.value, pca) are never rotated. Rotation redistributes variance among the rotated factors, so their individual variance percentages change while their sum (and cumvariance) is preserved.
m	the the match field: the common variable on both the table and spatial data. This name must be identical to both sets of data
f	The full path of csv file and the name of csv eg. C:/Users/owusu/Documents/Rpackages/qrfactor14/inst/ex
x	an object of class "qrfactor", i.e., a fitted model.
object	an object of class "qrfactor", i.e., a fitted model.
plot	The type of plots one desires. It takes "all" for all the 3 plots or "q" for q plot or "r" for r plot or 'qr' for both q and r plots
factors	list of factors one wants to plot. The default is factors=c(1,2). Please do not forget "c" in the list.
cex	A numerical value giving the amount by which plotting text and symbols should be magnified relative to the default. It also accepts a vector of values which are recycled eg cex=c("gold")
nfactors	The number of factors to extract
pch	Either an integer specifying a symbol or a single character to be used as the default in plotting points.
pos	The position of text labels
main	Main title of the graph
xlim	x-coordinates of the axis eg xlim=c(-1.5,1.5)
ylim	y-coordinates of the axis eg ylim=c(-1.5,1.5)
abline	the intercept and slope, single values of straight lines through the current plot. eg. abline(-0.5,0.5)
legend	position of legend: it takes topright, topleft, bottomright, bottomleft, top, left, bottom, right
legendvalues	The values of the legend
values	Incase one wants to label the graph with another variables. eg. values=c("gold")
nf	The number of factors to extract

rowname	rownames of the data
par	the layout setting in a form of list
verbose	logical; if TRUE, the analysis views (type = "cluster", "anova", "region", "admin", "diagnose") print their statistical tables (cluster means, ANOVA, Kruskal-Wallis, Tukey HSD, outliers) to the console. The default FALSE draws the plots silently, as R plot methods should. The plot() method also restores the user's par() settings on exit.
...	any other parameter can be added

Value

Objects of the class that basically list its elements

data	Original data for the model. All records must be numeric. It also accepts continuous data
gisdata	GIS data for the model incase you use shape files
x.standard	it is the scale matrix of the original data
correlation	The correlation matrix for the data
eigen.value	eigen value of correlation matrix of the data
eigen.vector	eigen vector of correlation matrix of the data
diagonal.matrix	diagonal matrix of eigen vector
pca	pca loadings
pcascores	PCA scores
r.loading	R-mode loadings
q.loading	Q-mode loadings
loadings	combined loadings of R and Q on the same axis
q.scores	computed Q-mode scores
scores	combined R-mode and Q-mode scores on the same axis
rownames	row names of the loadings
variables	variables names of the loadings, of the original data
rotation	the rotation actually applied to the loadings: "varimax" or "none"
unrotated.r.loading	the R-mode loadings before rotation (identical to r.loading when rotation = FALSE)
unrotated.q.loading	the Q-mode loadings before rotation (identical to q.loading when rotation = FALSE)

Author(s)

George Owusu

References

Bivand, R. S., Pebesma, E. J., Gomez-Rubio, V. (2008) Applied Spatial Data Analysis with R. Springer
 Kabacoff, I. R. (2011) R in Action. Data Analysis and Graphics with R. Manning Publications Co
 Kaiser, H. F. (1958) The varimax criterion for analytic rotation in factor analysis. Psychometrika 23(3):187-200

Examples

```
# --- CSV / data-frame workflow (fast, always runs) ---
csv <- system.file("external", "Africanfreshwater.csv", package = "qrfactor")
var <- c("Domestic", "Industry", "Agricultur", "Resources",
        "withdrawal", "perCapitaW")

mod0 <- qrfactor(csv, var = var) # classical unrotated solution (default)
mod0$r.loading
plot(mod0, rowname = "COUNTRY")

# opt in to a varimax rotation of the retained factors
rot <- qrfactor(csv, var = var, rotation = TRUE)
rot$rotation # "varimax"
rot$unrotated.r.loading # the unrotated loadings, same as mod0$r.loading

# per-cluster ANOVA / Kruskal-Wallis tables are printed only on request
plot(mod0, type = "cluster", verbose = TRUE)

# --- spatial workflow on the bundled shapefile (needs 'sf' and 'sp') ---
if (requireNamespace("sf", quietly = TRUE) &&
    requireNamespace("sp", quietly = TRUE)) {
  src <- system.file("external", package = "qrfactor")
  layer <- "Africanfreshwater"
  mod1 <- qrfactor(src, layer, var = var)
  plot(mod1, rowname = "COUNTRY")

  # join a CSV table to the shapefile on a common key
  mod3 <- qrfactor(src, layer, var = var, m = "COUNTRY", f = csv)
  plot(mod3, rowname = "COUNTRY", cex = c("means"),
       legend = "topleft", values = c("cluster"), pch = 23)

  plot(mod1, type = "map") # choropleth cascade of the factor indices
}
```

Description

It is for internal use only

Author(s)

George Owusu

Index

* **Factor Analysis**

qrfactor, [2](#)

* **Statistics**

rq, [5](#)

plot.qrfactor (qrfactor), [2](#)

print.qrfactor (qrfactor), [2](#)

qrfactor, [2](#)

rq, [5](#)

summary.qrfactor (qrfactor), [2](#)